

Tractor Pullers Rules

GOAL: For every competitor to have a fair chance and the safety of all pullers, promoters, and spectators. Have fun!

General safety issues:

- ALL TRACTORS ARE REQUIRED TO HAVE FENDERS OR SHIELDS
- Any driver assumed to be intoxicated will be disqualified
- Any driver will be disqualified if not seated at all times or if anything falls off the tractor while on the track
- No duals or chains allowed
- Front of weights must be no further than 13' ahead of the center of the rear axle.
- Up to 100lbs overage allowed in all tractor classes

FARM STOCK RULES

Factory stock size tires and rims (front and rear)—bias or radials. Factory stock engines, carburetors, injector pumps, RPMs—1% over factory specs, turbo—if factory equipped only. No cut tires. Working hydraulics and PTO. Unaltered factory drawbar and hitch assembly ONLY. NO loop drawbars! Two point hitches NEED to be pinned securely in position. MAX—20" drawbar height and 24" back from center of axle to drawbar. Twisted clevis ONLY. Weights must be secured properly. Engine side shields advised. **FENDERS OR SHIELDS REQUIRED ON ALL TRACTORS!**

HOT FARM RULES

Any cut tires allowed: 18.4-38 or 20.8-38 or 18.4-42. Radials allowed. Diesel only. Any diesel injection system allowed—Max P Pump 3000 or 7100. PTO and Hydraulics not required. Water injection or inter cooler (not both). Inter cooler allowed on tractors over 466 cu. Max of 650 cu. 18-20 draw bar rule with 3"

opening. Wheelie bars must be able to support the weight of the tractor, a 5" square pad—20" min outside to outside and be no more than 10" above ground, bars should extend 3" or more from the furthest rear radius point of the tire.

Kill switch-DIESEL TRACTORS MUST HAVE AIR SHUT OFF and able to pull from seat! Flywheel cover—blanket or 6" x 3/8 steel. Engine side shields. 3/8 Grade 5 bolt cross in exhaust pipe before elbow. NO curved stacks! Dead man throttle. Any block head manifolds from like mfg. allowed. No homemade manifolds! (Exception: Oliver's may run 5.9L Cummins)

Aluminum rear rims allowed. All tractors must have wide front end. Fenders required. ROPS with seatbelt or cage, helmets required with caged tractors, frame tie bars, electric fan OR 360 degree shield around OEM Fan of 1/8" thickness and SFI steel flywheels MANDATORY. Easily removable panels for Turbo inspections suggested!

Min. 2# Halon or 2.5# Dry fire extinguisher, 3000RPM Max-all tractors must have functional RPM monitoring device 2 prong 110 to hook to sled. Unit cost \$100 and can be purchased from Promoter or Dennis Frey @ 608643-3494 (First time pullers may hook once with RPM's checked by photo cell tach with a positive throttle stop at the injection pump before and after they hook.) Turbo: any turbo allowed. Turbo can be 3 x 3" max.

Pro-Farm Tractors

Water injection or inner cooler allowed, 20.8x 38 max tire size (bias or radial), any cut on tires, 20" draw bar height and 18" back from axle, 3000 RPM, 15 MPH, any fuel system, any Turbo.

Required: steel flywheel, steel shield or blanket, fenders, air shut off or kill switch, wheelie bars, side shields, dead-man throttle, roll bar or cage, tie bars, seat belt.

Trucks—Run What You Bring

Drivers must be 16 years or older and have a driver's license. No speed limits. No riders or weights in cab. Safety drive shaft chain advised for all pickups. Max drawbar height is 24". Seatbelt required.

Limited to first 10 trucks that sign up.