

MASTERS OF DISASTERS
STOCK MINI VANS, SUV,& COMPACT TRUCKS
2021 RULES

NO 04 OR NEWER DAKOTAS OR DURANGOS

1. No motor mount modifications. No welding or chaining of motor mounts. Can run 4,6 or 8 cylinders if motor is changed motor mounts must be bolted in. You may run headers if you want. Lower cradles ARE allowed and MUST BE bolted in ONLY, NO other modifications.
2. May use stock ignition or push button and toggle switch.
3. May use after market shifters..
4. Dash bars are optional.
5. You may weld rear ends.
6. No torching of fenders. Must be totally stock appearing minus the lights, chrome, etc.
7. Tire: Air tires only. Tubes and stem protectors will be allowed. Any 6 ply tire may run extra bead on outside of tire. You can run 8 inch or smaller centers.
8. Gas tanks and Battery boxes secured and covered inside car. All factory gas tanks must be removed from stock location.
9. Hoods may be fasten shut with (3 strands) #9 wire or chain (3/8) inch max. in 6 locations to sheet metal only, (2 may go to bumper) locations MAY NOY connect together, MUST be separate. NO HOOD BOLTS ALLOWED. Hoods WILL have large enough holes for fire extinguisher access, and MUST be open for inspection. NO bolting or screwing in hood openings.
10. FRONT BUMPER FASTENING No adding bumper brackets other than specified. Any automotive car bumper may be used bumpers must be cut down to fit width of car, seams may be welded. May use a completely flat 3x3 ¼ inch thick square tube inside bumper or attached to car (length of tube can be no wider than 3 inches wider than frame-rail on each side). Crush zone on front frame-rail may be removed, bumper shocks can be welded or removed, bumpers can be welded directly to frame. For mounting purposes u will be allowed to add a piece of tube 4x4- ¼ thick- 4 inch long max size that may be slid into frame and welded to your desired depth. U may also use the aid of a flat mount plate per frame-rail 5x5-1/4 thickness square plate to cap frame-rail to be able to attach bumper to car, weld them well we don't want any bumpers falling off.
MAX size for the bumper is 4"x 4" tubing.
IF THE RULES DO NOT SAY IT DO NOT ASSUME THAT YOU CAN DO IT, THIS IS A LOW BUDGET CLASS!!! JUDGES DECISION IS FINAL!!!
11. You can run a 4 point cage with plates no larger than 6x6
12. . You will be allowed a 4" diameter bar with 6"x6" plates on the ends mounted door to door behind the gas tank. This bar cannot be attached to any other interior bars, tank, coolers, or floor.

A TOTAL OF 6 PLATES PER VEHICLE WITH A 1 INCH GAP BETWEEN PLATES AND OR WELD.
PLATES MUST HAVE A ½" HOLE AND ON A BEND.

NO PLATES ON FRESH VEHICLES.

13. Doors must be chained or wired. 2 chains or wire per seam. Driver's door may be welded solid for driver's safety. 3 inch wide x 3/16 inch flat stock.

14. If you have a rusted away body mount, you will be allowed one chain loop or wire per mount to reconnect the body to frame. OR replace with a ½ inch bolt.

15. No auxiliary transmission coolers.

16. Must have 2 straps in front window.

17. NO ALL WHEEL DRIVES! In the mini class if you run a 4 wheel drive you must remove one of the drive shafts.